

RFID/ Prox Credentials

RFID/prox credentials can be used with any ZK readers which has an in-built a 125 KHz prox card reader.




Fob



Disc



Thick / Clamshell Card



Thin / ISO Card

Specifications

Interface

EM-4100 series prox cards with a EM/ Marin S.A. memory chip.
125 KHz (generic prox)
26-bit, Read-only
13.56 MHz (Mifare) Read-only
Passive prox/RFID responder

Dimensions

Thick clamshell card
Length: 3.36 inches (85.47 mm)
Width: 2.12 inches (53.85 mm)
Thickness: .077 inches (1.97 mm)
Badge clip slot: 0.63 inches X .13 inches

Key Fob size:
1.37 inches x .91 inches x .15 inches
34.8 mm x 23mm x 3.9 mm
RFID disk size:
Diameter: 7/8 inch (22.22mm)
Thickness: 1/16 inch (1.59mm)

Thin ISO card
Length: 3.36 inches (85.47 mm)
Width: 2.12 inches (53.85 mm)
Thickness: 0.03 inches (0.8 mm)
Badge clip slot: 0.63 inches X 0.13 inches
(16 mm X 3.30 mm)

For Any Further inquiry / assistance, contact us at

Bio Tech Systems

M-4/203, 2nd floor, Opposite Kerala School, Gupta Plaza, Vikaspuri, New Delhi-110018

Phone No. 011-45534875, 011-45566232,

Regd. Office: 81B/A1B, Paschim Vihar, New Delhi - 110063

Web Site: <http://biotechsystems.in>, E-Mail: contact@biotechsystems.in